

PMi 4500+HAU



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

FEATURES

- Inverter technology: stable power for safe operation of sensitive electronics.
- OHV engine provides consistent power for multiple applications.
- Low-oil level shutdown automatically safeguards engine from damage.
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
- ATS connector
- · Remote control
- 2 wire start
- · Lightweight and compact.
- Wheel kit integrated for easy transportation
- Fuel gauge allows user to track gasoline levels

1.1-	
Hz	50
V	230
	1
watt	4200
vatt	3800











Engine		
Brand		Pramac
Туре		OHV
Exhaust emission level		Stage V
Operating Speed Nominal	rpm	Variable
Fuel	'	Petrol
Starting Systems		Electric (+Recoil)
Oil capacity	I	0.78
Low Oil Shutdown		√
· · · · · · · · · · · · · · · · · · ·		



Alternator	
Voltage regulation system	Inverter

Dimensional data		
Length	(L) mm	578
Width	(W) mm	422
Height	(H) mm	500
Dry weight	kg	42.5
Carton box dimension LxWxH	mm	660x505x580



Autonomy		
Fuel tank capacity		12
Fuel consumption 50%	l/h	1.2
Running time 50% (Eco Mode)	h	9.7



Noise level		
Guaranteed noise level (LWA)	dB(A)	93
Noise pressure level @ 7 m	dB(A)	68

GENSET CONTROL

COMMANDS:

- Electric start button
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction
- ATS connector / 2 wire start / Remote control

INSTRUMENTATION:

- Voltage (V), Frequency (Hz), Running time (h)
- Oil alarming / output power
- Fuel level indicator on the tank
- 12V battery maintainer holder

PROTECTIONS

• Overcurrent / Overspeed / High temperature / AC thermal circuit breaker / DC circuit breaker

OUTPUT:

• DC12V 6A









SOCKET TYPE

AS/NZS 3112 15A 250V

2

The information is aligned with the Data file at the time of download. Printed on 10/11/2025 (ID 195853)

